SAFETY DATA SHEET



Date Prepared: 04/01/2014

MSDS No: 37

Date Revised: 07/22/2015

Revision No: 4

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT CODE: Touchstone Colorant, All Colors

MANUFACTURER

Bonstone Materials Corporation 707 Swan Drive Mukwonago, WI 53149

Emergency Contact: Mike Beckmann Emergency Phone: 262-363-9877

E-Mail: info@bonstone.com

24 HR. EMERGENCY TELEPHONE NUMBERS

Chemtrec: 1-800-424-9300

2. HAZARDS IDENTIFICATION

GHS LABEL

No GHS labelling is required for this product.

POTENTIAL HEALTH EFFECTS

EYES: Can cause severe irritation, redness, tearing, blurred vision.

SKIN: Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin

irritation and dermatitis (rash).

INGESTION: Substance may be harmful if swallowed. **INHALATION:** Prolonged inhalation may be harmful.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%
Tint resin	Trade secret

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Get immediate medical attention.

SKIN: Wash with soap and water. Get medical attention if irritation develops or persists.

INGESTION: Get medical attention immediately.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

5. FIRE FIGHTING MEASURES

GENERAL HAZARD: During a fire, irritating and highly toxic gases may be generated by thermal decomposition or

combustion.

EXPLOSION HAZARDS: None known. Treat as combustible.

FIRE FIGHTING PROCEDURES: Use dry chemical, alcohol foam or CO2. Water or foam may cause frothing. Firefighters and others who may be exposed to products of combustion should wear full firefighting turnout gear and self-contained breathing apparatus. Firefighting equipment should be thoroughly decontaminated after use.

FIRE EXPLOSION: None known. Treat as combustible.

6. ACCIDENTAL RELEASE MEASURES

GENERAL PROCEDURES: Stop the leak, if possible. Shut off or remove all ignition sources. Construct a dike to prevent spreading (includes molten liquids until they freeze).

RELEASE NOTES: Notify authorities if any exposures to the general public or environment occurs or is likely to occur.

SPECIAL PROTECTIVE EQUIPMENT: Remove contaminated clothing and wash before reuse.

COMMENTS: If recovery is not feasible, admix with dry soil, sand or non-reactive absorbent and place in an appropriate chemical waste container. Transfer to containers by suction, preparatory for later disposal. Place in metal containers for recovery or disposal. Flush area with water spray. Clean-up personnel must be equipped with self-contained breathing apparatus and butyl rubber protective clothing. For large spills, recover spilled material with a vacuum truck.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Use with adequate ventilation.

HANDLING: Keep away from heat, sparks and flame.

STORAGE: Store in a tightly closed container.

COMMENTS: Follow all MSDS/label precautions even after container is emptied because they may retain product

residues.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: Use only in a well ventilated area.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

SKIN: Where splashing is possible, full chemically resistant protective clothing (e.g. acid suit) and boots are required.

RESPIRATORY: NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

WORK HYGIENIC PRACTICES: Provide readily accessible eyewash stations and safety showers. Wash at the end of each work shift and before eating, smoking, or using the toilet.

OTHER USE PRECAUTIONS: Where contact is likely, wear chemical resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield.

COMMENTS: Avoid breathing any (dust, vapor, mist, gas) that may be generated when grinding cured material.

9. PHYSICAL AND CHEMICAL PROPERTIES

Chemical Name	Flash Point (°C)	Solubility in Water
Tint resin	302	Negligible

PHYSICAL STATE: Liquid

APPEARANCE: Viscous liquid

COLOR: Various

FLASHPOINT AND METHOD: (302°F)

FLAMMABLE LIMITS: 0 to 0

SOLUBILITY IN WATER: Negligible

DENSITY: 13.7

SPECIFIC GRAVITY: 1.6 (VOC): ~ to 0.12 lbs/gal

10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: Stable.

CONDITIONS TO AVOID: Heat, fire, severe oxidizing conditions, and/or excessive moisture.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide, carbon monoxide, aldehydes, carbon, and other

toxic gases.

INCOMPATIBLE MATERIALS: Will react exothermally with isocyanates. Avoid oxidizing agents and strong

alkalies.

11. TOXICOLOGICAL INFORMATION

SKIN EFFECTS: May cause severe injury to skin following prolonged or repeated contact, and may cause skin sensitization or other allergic responses.

GENERAL COMMENTS: Not determined.

12. ECOLOGICAL INFORMATION

COMMENTS: No information.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Recover, reclaim or recycle when practical. Dispose of in accordance with federal, state and local regulations. Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information incomplete, inaccurate, or otherwise inappropriate. Furthermore, state and local waste disposal requirements be be more restrictive or otherwise different from federal laws and regulations.

14. TRANSPORT INFORMATION

COMMENTS: Not regulated by DOT

15. REGULATORY INFORMATION

UNITED STATES

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA STATUS: This product and/or all of it's components is/are listed on the TSCA Inventory.

16. OTHER INFORMATION

REASON FOR ISSUE: New MSDS format

APPROVED BY: Mike Beckmann **TITLE:** President

Date Revised: 07/22/2015

INFORMATION CONTACT: Mike Beckmann

REVISION SUMMARY: This SDS replaces the 04/01/2014 SDS. Revised: **Section 1:** PRODUCT CODE, REASON FOR ISSUE. **Section 2:** . **Section 3:** Wt.%. **Section 9:** COLOR, PERCENT VOLATILE, VAPOR DENSITY, VAPOR PRESSURE.

MANUFACTURER DISCLAIMER: The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or any process, unless specified in the text.