

511 Spray-On Grout Sealer

Natural Look Penetrating Sealer

Water & Stain Protection for

- New Grout
- Natural Stone
- Old Grout

Will not Harm Ceramic Tile, Porcelain Tile, Glazed Tile, Quarry Tile, Glass or Plastic Tile, Marble, Granite, Limestone, Travertine, Slate, other Natural Stone

Uses

- Interior & Exterior
- Restrooms
- Kitchen
- Anywhere you use Grout
- Showers

Special Features

- Easy To Use "Clean Hands" Approach
- Apply as little as 2 hours after Grouting
- Low Toxicity
- Stain Resistant
- Economical
- Recyclable (doesn't end up in a landfill)
- Directional Spray
- Weather Resistant
- Non Yellowing
- U.V. Transparent
- Tamper Proof Container

KEEP OUT OF REACH OF CHILDREN. This product is formulated for sealing all types of new and old grout to provide resistance against water, oils, alkalis, acids, and staining. **511 Spray-On Grout Sealer** is a unique formulation designed for the protection of all types of grout both new and old. **511 Spray-On Grout Sealer** penetrates into the surface and forms an invisible barrier that is resistant to moisture and stains, while allowing vapor to escape. **511 Spray-On Grout Sealer** is not a surface coating and will not alter the natural look while making the grout easier to clean. **511 Spray-On Grout Sealer** can be applied to freshly installed grout as quickly as 2 hours after grouting. **511 Spray-On Grout Sealer** can be used on interior and exterior applications. **511 Spray-On Grout Sealer** is U.V. transparent and will not yellow under any circumstances. **511 Spray-On Grout Sealer** averages five to twenty times the coverage of competitive products. (See coverage chart). **511 Spray-On Grout Sealer** uses a "Clean Hands" approach to grout sealer application and has a unique directional spray allowing the user to apply the sealer without touching their hands.

Test Data

511 Spray-On Grout Sealer HAS BEEN TESTED BY SCIENTIFIC CERTIFICATION SYSTEMS PASSING THE MOST STRINGENT CALIFORNIA AIR RESOURCES BOARD (CARB) SECTION 01350 TEST AND HAS RECEIVED INDOOR ADVANTAGE GOLD CERTIFICATION.

Sample Testing

Due to the differences of each grout, several inconspicuous test patches should be completed to assure maximum performance. **User must determine suitability of the product for their intended use.**

Color Enhancement

For added color with "TEXTURED AND NON POLISHED" surfaces, **511 Seal & Enhance** may be applied as directed.

Gloss Enhancement

For a higher gloss finish on POLISHED stone surfaces, use **Water Ring & Etch Remover**, **Marble Conditioner**, **Mira Dust**, **Mira Polish** or **Granite Brite**. For counters and furniture, use **Stone Polish**. For tile surfaces, try **Tile Brite**.

Protect Neighboring Surfaces

Always protect neighboring surfaces including wood, carpet, metal, landscaping and other non-masonry surfaces.

NEW INSTALLATIONS - APPLICATION INSTRUCTIONS

Read entire label and SDS/PDS before using. **511 Spray-On Grout Sealer** should not be diluted or thinned in any way. **511 Spray-On Grout Sealer** should be used as is direct from approved container.

After Grouting: Once grouted, make sure that all grout residue is removed from the surface with a clean sponge and water. Allow grout to cure per manufacturers specification or at least 2 hours. If grout clean up is not performed effectively, an additional cleaning may be necessary to remove remaining grout residue or haze. For this procedure use **Phosphoric Acid Cleaner**, (**HDAC Heavy Duty Acidic Cleaner (Hydrochloric Acid)**) or **Epoxy Grout Film Remover** following the instructions carefully. Once the cleaned area has completely dried, proceed with the sealing of the grout for water and stain resistance. Apply **511 Spray-On Grout Sealer** to all grout with the unique "Clean Hands" Spray. Any excess sealer that gets on the surface should be wiped off with a clean towel before it dries.

Existing Installation - Surface Preparation

Surface must be dry and free of contaminants, including previously applied sealers, dirt, lime & hard water deposits, efflorescence, rust and other heavy dirt and grime.

Surface Coating/Wax Removal: To remove existing coatings and/or waxes, use **Mira Strip** or **Finish Sealer Stripper** as directed.

Heavy Duty Cleaning: To remove lime and hard water deposits, efflorescence, rust, grease and other heavy dirt and grime use **HDAC (Heavy Duty Acidic Cleaner)** or **Phosphoric Acid Cleaner** as directed.

For a non-acid deep clean use **Liquid Powlitice** as directed.

Light Cleaning: Use **Tile & Stone Cleaner**, **Porcelain & Ceramic Tile Cleaner**, **Limestone/Travertine Soap** or **Counter Kleen** as directed.

Existing Installation - Application Instructions

Once all grout and surrounding surfaces are clean, proceed with the application instructions previously mentioned.

Residue Removal

To remove accumulated **511 Spray-On Grout Sealer**, use **Miracle Residue Remover** as directed.

Cure Time

511 Spray-On Grout Sealer will be dry to the touch in 1 - 3 hours and may be used for normal foot traffic. For optimum results the area should be kept dry and free from staining materials for 72 hours.

Coverage: Used as directed, **511 Spray-On Grout Sealer** will cover up to 250 linear feet of grout.

Cost per linear foot: Approximately 5 cents per foot.

MAINTENANCE

For ongoing maintenance instructions please refer to Miracle Sealants Care Guide. Refer to the Miracle Sealants Product Recommendation Chart for specific product recommendations.

Storage

Store **511 Spray-On Grout Sealer** in the original sealed container. Stored at 77° F (25° C), **511 Spray-On Grout Sealer** will have a shelf life of 24 months.

Technical Support

For additional technical support, contact Miracle Sealants Company at 1-800-350-1901 or 626-443-6433 ext. 3013

Office Hours

Monday - Friday from 8:30 am - 5:00 pm PT.
1-626-443-6433 1-800-350-1901 • Fax: 1-626-443-1435
Website: www.miraclesealants.com

Product Damaged During Transportation

If product is damaged during transportation contact Info Trac @ 1-800-535-5053

Additional Product

Miracle Sealants Company offers a complete line of water and stain repellents, sealers, cleaners, polishing compounds, diamond abrasives, machinery and accessories for the tile, stone, concrete, metal, fabric and carpet professional or do-it-yourself specialist.

Warranty

Instructions are a condensed guide and should not be considered complete. In the event of failure, the only obligation of Miracle Sealants Company shall be to replace such products proven to be defective. Before using, user shall determine the suitability of the product for their intended use. User assumes all risks and liability whatsoever in connection therein. Neither seller nor manufacturer shall be liable for any injury or inability to use this product.

Caution

511 Spray-On Grout Sealer contains combustible petroleum distillates. All solvents must be considered toxic and must be used in a well-ventilated area. Good ventilation means that fresh air is flowing in such a way as to feel a slight breeze. Open windows and use fans to circulate air. Continue to ventilate until vapors are eliminated. Exposure to high vapor concentration must be avoided. Inhaling the vapors can be harmful. Keep away from heat and open flames. Avoid prolonged contact with skin. Chemical resistant gloves should be worn at all times. Keep small children and pets out of the area until product or surface has thoroughly dried. Refer to the MSDS for additional information.