



Premium Building Products
That Protect

#6000 PRIMER PRODUCT DATA SHEET

DESCRIPTION:

#6000 Primer is a high tack water based primer concentrate for use in indoor applications.

Store product at 40°F or above; do not allow primer to freeze.

RECOMMENDED USES:

Products	Application	Coverage
<ul style="list-style-type: none">• AFM	For horizontal applications between 45°F and 120°F.	up to 500 square feet per gallon (depending on porosity of the substrate)
<ul style="list-style-type: none">• AFM-WM	For horizontal applications between 45°F and 120°F.	up to 500 square feet per gallon (depending on porosity of the substrate)
<ul style="list-style-type: none">• Any other Protecto Wrap products	For interior applications	up to 500 square feet per gallon (depending on porosity of the substrate)

*For vertical applications, coverage is up to 200 square feet per gallon depending on the substrate's porosity.

PROPERTIES:

Adhesion to steel	Excellent
Adhesion to concrete	Excellent
Adhesion to wood	Excellent
Adhesion to membrane	Excellent
Shelf life (min.)	One year
Tack free time (minutes)	15-45 minutes
VOC Compliant	



Premium Building Products
That Protect

DIRECTIONS FOR USE:

PREPARATION:

- The surface shall be cleaned by brooming, vacuuming or high pressure clean dry air so that all dirt, dust, loose concrete, or other contaminants that may adversely affect the adhesion of the membrane are removed.
- For horizontal applications, the primer can be mixed at a ratio of 1 part concentrate to 2 parts clean water.
- For vertical applications, the primer is to be in full strength concentrate form. Do not dilute.
- On porous or weathered surfaces, the concentrate should be used full strength.
- Mix the primer thoroughly. Should the primer be left to sit for an extended period of time, thoroughly re-mix before use.

APPLICATION:

- Apply primer to all surfaces by roller or brush.
- The primer must be allowed to fully dry before installation of the product – do not cover wet primer. When fully cured, it will feel tacky to the touch, but will not come off the surface.
- Prime only as much area as can be covered in half a day's work. Re-prime areas not covered in half a day's work with a light coat of #6000 Primer.

NOTE:

- Do not allow primer to freeze.
- Shake well before using and keep stirred during application.

PACKAGING AND WEIGHTS:

Quantity	Packaging	Weight
16 oz bottles	9 bottles/carton	9 lbs.
1 U.S. gallon	4 gallons/carton	34 lbs.

PROTECTO WRAP COMPANY
1955 South Cherokee Street
Denver, CO 80223
(303) 777-3001 • (800) 759-9727
FAX (303) 777-9273
www.protectowrap.com