

ARDEX SK 175™

Waterproofing Membrane and Vapor Retarder for Tile & Stone Installations

ARDEX SK 175 is a pliable, sheet-applied, bonded waterproof membrane and vapor retarder constructed of polyethylene. Its high-performance fleece webbing securely bonds the membrane using ARDEX mortars prior to the installation of tile or stone in areas requiring topside waterproofing and enhanced vapor protection. Tile can be installed directly onto ARDEX SK 175.

Key Features

- For topside waterproofing over floors and walls
- Very low perm rating acceptable for residential and commercial steam showers (.04)
- Interior and exterior use
- Ideal for swimming pools; just one layer required
- Use on balconies and terraces

Accessories

- ARDEX SK 175™ Seam Tape
- ARDEX SK 175™ Inside Corners and Outside Corners
- ARDEX SK 175™ Pipe Collar

Installation

Install Tile: 3 to 12 hours

(see approved ARDEX mortar tech data sheet)

Packaging:

Waterproofing Membrane 39" wide x 33' long
(1 m wide x 10 m long) roll

Waterproofing Membrane 39" wide x 98' long
(1 m wide x 30 m long) roll

ARDEX SK 175 Seam Tape 4.75" wide x 16' long
(12.1 cm wide x 5 m long) roll

ARDEX SK 175 Seam Tape 4.75" wide x 98' long
(12.1 cm wide x 30 m long) roll

Performance

Flood Test: 24 hours after installation

SystemOne™



Refer to the technical data sheet at www.ardexamericas.com or call 888-512-7339 prior to installation. For free ARDEX product training click on ARDEX Academy.

For easy-to use ARDEX Product Calculators and Product Information On the Go, download the ARDEX App at:



WATERPROOFING SYSTEMS



888-512-7339
+1-724-203-5000
www.ardexamericas.com