

COMBICUT 200 VA



TOGETHER WE BUILD

TILE STONE AND PORCELAIN SAWS



NOISE LEVEL
<78 DB

COMBICUT 200 VA | Model # 1188084 | 110V/60Hz, 1.75 HP

ACCURATE, LIGHTWEIGHT RAIL SAW

Easy to use and built to last. The perfect solution for rental stores as the Combi 200VA is equally at home in the hands of the professional installer, contractor or the Do-It-Yourselfer.

Water valve to control water mist

8" continuous rim porcelain blade included

Complete with high flow water pump

Included side table for extra work space

Included protractor up to 180°

ONLY
48 lbs

High impact removable poly water pan with baffles

PLUNGE CUTS

Plunge cuts are smooth and precise as the cast aluminum cutting head pivots on a sealed bushing. "L" cuts for door jams are now quick n' simple.




ACCURATE ANGLED CUTS

When 45 degree cuts are needed, just tilt the travel beam. Simple and accurate. While the overhead beam design provides a smooth accurate cut.



STAND INCLUDED



INNOVATION

The cast aluminum protractor is the only truly accurate rip guide in the industry.



TILE CLAMP FOR ACCURACY

The tile clamping system is an accessory that attaches to all Combicut Series saws. Clamp down tiles and use the overhead laser to guarantee a smooth, thorough, and accurate cut. Item # 1188157



CAST ALUMINUM

The cast aluminum construction of the Combicut VA's frame structure ensures a rigid, yet light weight saw. Out of the box it can cut tile or stone to within 1/32"

COMBICUT 250 VA



TILE STONE AND PORCELAIN SAWS

TOGETHER **WE BUILD**



COMBICUT 250 VA | Model # 1188164 | 110V/60Hz, 1.75 HP



Water valve to control water mist

10" continuous rim porcelain blade included

Complete with high flow water pump

Included side table for extra work space

Included protractor up to 180°

Equipped with a laser guide to make cuts quickly and accurately

High impact removable poly water pan with baffles

Lightweight folding stand included

ONLY 72 lbs

Technical specifications

	COMBI 200VA 8"	COMBI 250VA 10"
Blade diameter	8 in	10 in
Blade shaft diameter	5/8 in	5/8 in
Max. cutting length (w/plunge cut)	21 (24) in	28 (31) in
Max. cutting depth	2-3/4 in	3-3/4 in
Motor rating	1.75 hp 110v, 15 amp	1.75 hp 110v, 15 amp
Blade speed	2800 rpm	2800 rpm
Weight (boxed, includes stand)	48 (68) lbs	72 (85) lbs
Water pan capacity	5 gal	10 gal
Water pump flow	3 gpm	3 gpm
Length* (boxed)	35 (37) in	40 (43) in
Height* (boxed)	19 (22) in	22 (24) in
Width* (boxed)	18 (20) in	18 (21) in
● Replacement Blade - Continuous Rim	#1193920	#1193922
● Replacement Blade - Abrasive Masonry	n/a	#1193932
● Replacement Blade - Concrete Turbo	n/a	#1193942

(* Operating Dimensions (boxed))

PERFORMANCE

To ensure that the Combi 200VA and 250VA would be both light and powerful, we designed and developed an all new 1.75 HP motor. Cuts are made quickly and quietly. Performance and reliability are guaranteed.

EQUIPPED WITH A LASER GUIDE

A laser cutting guide comes standard with every Combi cut 250VA. Mark the line of your cut on the material, line it up with the laser, and go.

