

SAFETY DATA SHEET

1. Identification

Product identifier LATICRETE 253 Gold Rapid

Other means of identification Not available.

Recommended use Tile adhesive.

Recommended restrictions Workers (and your customers or users in the case of resale) should be informed of the potential

presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required

under applicable regulations.

Manufacturer / Importer / Supplier / Distributor information

Company Name
Address
LATICRETE International
1 Laticrete Park, N
Bethany, CT 06524

Telephone (203)-393-0010
Contact person Steve Fine
Website www.laticrete.com

Emergency phone number Call CHEMTREC day or night

USA/Canada - 1.800.424.9300 Mexico - 1.800.681.9531 Outside USA/Canada 1.703.527.3887

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 1
Sensitization, skin Category 1
Carcinogenicity Category 1A
Reproductive toxicity Category 1B

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Specific target organ toxicity, repeated Category 2 (lung)

exposure

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May

cause cancer. May damage fertility or the unborn child. May cause respiratory irritation. May

cause damage to organs (lung) through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe dust/fume. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Contaminated work clothing must not be allowed out of the workplace.

Response If inhaled: Remove person to fresh air and keep comfortable for breathing. If on skin: Wash with

plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off

contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a

poison center/doctor.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

Not classified.

LATICRETE 253 Gold Rapid SDS US

916450 Version #: 01 Revision date: - Issue date: 21-November-2013

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Silica Sand	14808-60-7	55 - 60
Portland Cement	65997-15-1	14 - 22
Calcium aluminate cement	65997-16-2	8 - 12
Lithium Carbonate	554-13-2	0.25 - 0.35

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a physician

if symptoms develop or persist.

Skin contact

Wash off with soap and plenty of water. If skin irritation or rash occurs: Get medical

advice/attention. Take off contaminated clothing and wash before reuse.

Eye contact

Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control

center immediately.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Rash. Coughing. Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special

treatment needed **General information** Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

None known.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment

and precautions for firefighters

Fire-fighting

equipment/instructions

In case of fire and/or explosion do not breathe fumes.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep upwind. Avoid formation of dust. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk. Sweep or shovel up material and place in a clearly labeled container for waste. Collect dust using a vacuum cleaner. Following product recovery, flush area with water.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Wear appropriate personal protective equipment. Do not breathe dust. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Keep container tightly closed. Store in a cool, dry place out of direct sunlight.

LATICRETE 253 Gold Rapid SDS US

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form	
Portland Cement (CAS 65997-15-1)	PEL	5 mg/m3	Respirable fraction.	
•		15 mg/m3	Total dust.	
US. OSHA Table Z-3 (29 C	CFR 1910.1000)			
Components	Туре	Value	Form	
Portland Cement (CAS 65997-15-1)	TWA	50 millions of particle		
Silica Sand (CAS 14808-60-7)	TWA	0.3 mg/m3	Total dust.	
		0.1 mg/m3	Respirable.	
		2.4 millions of particle	Respirable.	
US. ACGIH Threshold Lin	nit Values			
Components	Туре	Value	Form	
Portland Cement (CAS 65997-15-1)	TWA	1 mg/m3	Respirable fraction.	
Silica Sand (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.	
US NIOSH Pocket Guide	to Chemical Hazards: Recommended e	xposure limit (REL)		
Components	Туре	Value	Form	
Portland Cement (CAS 65997-15-1)	TWA	5 mg/m3	Respirable.	
		10 mg/m3	Total	
Silica Sand (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.	
ogical limit values	No biological exposure limits noted for	or the ingredient(s).		
osure guidelines	Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.			
propriate engineering trols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.			
vidual protection measure	es, such as personal protective equipm	ent		
Eye/face protection	Wear safety glasses with side shields	s (or goggles).		
		* =		

In

Skin protection

Hand protection Wear chemical-resistant, impervious gloves. Other Wear appropriate chemical resistant clothing.

Respiratory protection Wear a dust mask if dust is generated above exposure limits. Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the

1/-1--

Form

workplace.

9. Physical and chemical properties

Appearance

Physical state Solid. **Form** Powder.

Color Gray or off-white.

Odor Odorless. **Odor threshold** Not available. Not available. pН Melting point/freezing point Not available.

LATICRETE 253 Gold Rapid SDS US

916450 Version #: 01 Revision date: - Issue date: 21-November-2013

Initial boiling point and boiling

range

Not flammable or combustible. Flash point

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available.

Vapor pressure Not available. Not available. Vapor density 1.2 - 1.5Relative density Solubility(ies) Insoluble Not available. Partition coefficient

(n-octanol/water)

Not available. **Auto-ignition temperature** Not available. **Decomposition temperature Viscosity** Not available.

Other information

0 % VOC (Weight %)

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Swallowing may cause gastrointestinal irritation. Ingestion

Dust irritates the respiratory system, and may cause coughing and difficulties in breathing. Inhalation Skin contact Causes skin irritation. May cause an allergic skin reaction. Prolonged contact with wet

cement/mixture may cause burns.

Causes serious eye damage. Prolonged contact with wet cement/mixture may cause burns. Eye contact

Symptoms related to the physical, chemical and toxicological characteristics Rash. Coughing. Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may cause chronic effects.

Information on toxicological effects

May cause respiratory irritation. Acute toxicity

Components **Species Test Results**

Lithium Carbonate (CAS 554-13-2)

Acute

Inhalation

Rat LC50 > 2.17 mg/l, 4 Hours

Oral

LD50 Rat 525 mg/kg

Skin corrosion/irritation Causes skin irritation.

LATICRETE 253 Gold Rapid SDS US Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory sensitization

No data available.

Skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

May cause cancer. In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003)

IARC Monographs. Overall Evaluation of Carcinogenicity

Silica Sand (CAS 14808-60-7) 1 Carcinogenic to humans.

NTP Report on Carcinogens

Silica Sand (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicityMay damage fertility or the unborn child.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

May cause damage to organs (lung) through prolonged or repeated exposure.

Aspiration hazard Due to the physical form of the product it is not an aspiration hazard.

Chronic effects Prolonged or repeated exposure may cause lung injury, including silicosis.

12. Ecological information

Ecotoxicity Not expected to be harmful to aquatic organisms.

ProductSpeciesTest ResultsLATICRETE 253 Gold Rapid (CAS Mixture)AquaticFishLC50Fish8303.9492 mg/l, 96 hours, estimatedComponentsSpeciesTest Results

Lithium Carbonate (CAS 554-13-2)

Aquatic

Fish LC50 Mummichog (Fundulus heteroclitus) 8.1 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available for this product.

Mobility in soil The product is not mobile in soil.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsDispose of contents/container in accordance with local/regional/national/international regulations.

Do not contaminate ponds, waterways or ditches with chemical or used container.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

LATICRETE 253 Gold Rapid SDS US

14. Transport information

DOT

Not regulated as a hazardous material by DOT.

IATA

Not regulated as a dangerous good.

IMDG

Not regulated as a dangerous good.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code This substance/mixture is not intended to be transported in bulk.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely

У

hazardous substance

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug

Not regulated.

Administration (FDA)

US state regulations WARNING: This product contains chemical(s) known to the State of California to cause cancer

and birth defects or other reproductive harm.

US. Massachusetts RTK - Substance List

Lithium Carbonate (CAS 554-13-2) Portland Cement (CAS 65997-15-1) Silica Sand (CAS 14808-60-7)

US. New Jersey Worker and Community Right-to-Know Act

Lithium Carbonate (CAS 554-13-2) 500 lbs

US. Pennsylvania RTK - Hazardous Substances

Portland Cement (CAS 65997-15-1) Silica Sand (CAS 14808-60-7)

US. Rhode Island RTK

Lithium Carbonate (CAS 554-13-2)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Lithium Carbonate (CAS 554-13-2) Silica Sand (CAS 14808-60-7)

LATICRETE 253 Gold Rapid SDS US

916450 Version #: 01 Revision date: - Issue date: 21-November-2013

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 21-November-2013

Revision date - 01

NFPA Ratings



References HSDB® - Hazardous Substances Data Bank

Registry of Toxic Effects of Chemical Substances (RTECS)

Disclaimer The information in this (M)SDS was obtained from sources which we believe are reliable but

cannot guarantee. Additionally, your use of this information is beyond our control and may be beyond our knowledge. Therefore, the information is provided without any representation or

warranty express or implied.

LATICRETE 253 Gold Rapid SDS US

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).