

Masterboard™

Joint Sealant



Contains 10.5 FL OZ
(310 ml)

Masterboard™

Master Wholesale Inc.
520 S Front St, Seattle WA 98108
(800) 938-7925
www.masterwholesale.com



Item# MWH-00003



Masterboard™ Joint Sealant is designed for high strength and adhesion, flexibility and waterproofing of connections and seams in Masterboard™ product system assemblies. The modified silane (MSP) sealant and adhesive is designed to work with Masterboard™ Tile Backer's XPS foam cell structure and its specific cementitious coating alike. Tested and proven as a system assembly optimized to perform long-term in wet and alkaline environments such as under thinset tile adhesive layers.

Precautionary Statement

- Keep out of reach of children.
- Obtain special instructions before use.
- Wear protective gloves/protective clothing/eye protection/face protection. Provide adequate ventilation. Do not breathe dust/fume/gas/mist/vapor/spray.
- Wash hands and face thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.
- Wash clothing before reuse.
- Do not release to the environment. Store locked up and dispose of contents/ container to hazardous or special waste collection point.
- Refer to the First Aid Procedures for specific treatment on this label.
- Refer to Safety Data Sheet for detailed information.

First Aid Procedures

Eye Contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice/attention.

Skin Contact: Immediately clean with water and soap followed by thorough rinsing. Take off contaminated clothing. Get medical advice/attention.

Inhalation: Move victim to fresh air. Seek medical treatment in case of troubles.

Ingestion: Do not induce vomiting. Seek medical advice/attention immediately.

Get medical advice/attention if exposed or concerned. Have product container or label at hand.

In case of an emergency, please contact
Chentrec: +1 703-741-5970

Contents: CAS# 1317-65-3 Calcium carbonate,
Carbonic acid/calcium salt (1:1), 13463-67-7,
2768-02-7, 818-08-6, 28553-12-0, 1333-86-4.



Danger: Causes serious eye irritation. May cause an allergic skin reaction. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.

 **WARNING:** Cancer and Reproductive Harm
- www.P65Warnings.ca.gov

Masterboard™ Joint Sealant está diseñado para una alta resistencia y adherencia, flexibilidad e impermeabilización de las conexiones y juntas en los ensamblajes de los sistemas de productos Masterboard™. El sellador y adhesivo de silano modificado (MSP) está diseñado para trabajar con la estructura celular de espuma XPS de Masterboard™. Tile Backer y su revestimiento cementoso específico por igual. Probado y comprobado como un conjunto deMeYa sistema optimizado para funcionar a largo plazo en entornos húmedos y alcalinos, como debajo de capas adhesivas de baldosas thinset.

Indicaciones de precaución

- Mantener fuera del alcance de los niños.
- Procurar instrucciones especiales antes de usar.
- Llevar guantes de protección, ropa de protección, protección para los ojos y protección para la cara. Proporcionar ventilación adecuada. No inhalar polvo, humo, gas, niebla, vapores o aerosol.
- Lavar a fondo las manos y la cara antes de manipular. La ropa de trabajo contaminada no debe sacarse del lugar de trabajo. Lavar la ropa antes de volver a usar.
- No descargar en el medio ambiente. Almacenar bajo llave y deshacerse del contenido y el envase en un lugar de recogida de desechos especiales o peligrosos.
- Consultar el tratamiento específico en los procedimientos de primeros auxilios que indica esta etiqueta.
- Consultar información detallada en la ficha de datos de seguridad.

Procedimientos de primeros auxilios

Contacto con los ojos: Lavar de inmediato los ojos con abundante agua corriente de 10 a 15 minutos manteniendo separados los párpados. Si corresponde, quitarse los lentes de contacto si resulta fácil hacerlo. Seguir enjuagando. Buscar el consejo o la atención de un médico.

Contacto con la piel: Lavar de inmediato con agua y jabón y, seguidamente, enjuagar. Quitarse la ropa contaminada. Buscar el consejo o la atención de un médico.

Inhalación: Sacar la víctima al aire libre. Procurar tratamiento médico si surgieran dificultades.

Ingestión: No provocar el vómito. Buscar de inmediato el consejo o la atención de un médico.

Buscar el consejo o la atención de un médico en caso de exposición manifiesta o presunta. Tener a mano el envase o la etiqueta del producto.

En caso de emergencia, contacte a
Chentrec: +1 703-741-5970

Contenido: CAS# 1317-65-3 carbonato de calcio, ácido carbónico/sal de calcio (1:1), 13463-67-7, 2768-02-7, 818-08-6, 28553-12-0, 1333-86-4.

Peligro: Produce irritación ocular grave. Puede producir una reacción alérgica cutánea. Se sospecha que tenga efectos perjudiciales en la fertilidad o el feto. La exposición prolongada o repetida puede producir daños en los órganos. Nocivo para la vida acuática con efectos duraderos.

 **ADVERTENCIA:** Cáncer y daño reproductivo - www.P65Warnings.ca.gov