

PRODUCT FEATURES



**Vibration Reducing Handle Bars**

Shock-absorbing handle bars reduce vibrations up to 40%.



**Quick Belt Tensioning**

Provides fast and accurate belt tensioning.



**Fast Blade Guard Lock**

No hassle, blade guard securing lock.



The next generation of 13HP saws. The C1318P features shock-absorbing handle bars. The new sleek design of the water tank, with increased capacity and improved securing, adds an additional 6.5 gallons of water over the cut. And, a newly-designed belt tensioning system helps keep the saw cutting true and true. All these features, coupled with the Honda 13HP engine, makes the C1318P the premiere choice for rental and service work.

**TECHNICAL SPECIFICATIONS**

PRODUCT #	C1318P
UPC	70184642453
Blade Guard Capacity – in (mm)	18" (457)
Maximum Depth of Cut – in (mm)	6-5/8" (168)
Arbor Size – in (mm)	1" (25)
Blade Flange Diameter – in (mm)	4-1/2" (114)
Blade Shaft RPM	2,573
Blade Shaft Diameter – in (mm)	1.18" (30)
Blade Shaft Bearings	Heavy Duty Pillow Block
Blade Shaft Drive	Single 10 Groove Belt
Blade Guard Attachment	Hinged, All Steel
Blade Control	Hand Wheel/Screw Feed
Axle – Front – in (mm)	25/32" (20)
Axle – Rear – in (mm)	25/32" (20)
Wheels – Front D x W x B – in (mm)	4-59/64" x 1-31/32" x 25/32" (125 x 50 x 20)
Wheels – Rear D x W x B – in (mm)	8" x 1-1/4" x 25/32" (203 x 32 x 20)
Handle Bars/Adjustment Length	6-1/4" (160)
Control	5.28 gal. (20 l)
Speed	Push
Chassis	Heavy Duty Steel Box with Longitudinal and Horizontal Reinforcements
Power Source	Gasoline, Single Cylinder 4 Cycle
Engine Type	Honda GX390
Specifications	GX390K1QXC9
Maximum Horsepower*	13 HP (9.5kW)
Net Horsepower*	11 HP (8.2 kW)
Displacement – cu In (l)	23.7 cu in (0.39 l)
Bore – in (mm)	3.5" (88)
Stroke – in (mm)	2.5" (64)
Cylinders/Cycle	Single Cylinder 4 Cycle
Fuel Capacity – gal (l)	1.79 gal. (6.5 l)
Oil Capacity – qt (l)	1.16 qt. (1.1 l)
Air Filter	Four Stage Cyclone
Starter	Manual
Engine Cooling	Forced Air
SAW DIMENSIONS	
Height	39" (990)
Minimum Saw Length (Transport) – in (mm)	33-1/2" (850)
Maximum Saw Length (Working) – in (mm)	61-1/2" (1,561)
Maximum Pointer Length – in (mm)	20-7/8" (528)
Frame Width – in (mm)	16-1/2" (421)
Saw Width – in (mm)	22" (609)
Front (Outside to Outside Wheel Width) – in (mm)	10-7/16" (265)
Rear (Outside to Outside Wheel Width) – in (mm)	16-57/64" (429)
Blade to Wall – in (mm)	4-1/2" (114)
Wheel Base Length – in (mm)	13" (332)
Weight Crated – lbs. (kg)	240 (109)
Weight Uncrated – lbs (kg)	220 (100)

\*= DATA PROVIDED BY MOTOR/ENGINE MANUFACTURER

**GENUINE NORTON CLIPPER DIAMOND BLADE INCLUDED WITH SAW.**



Visit our YouTube page for more product information at:  
[www.youtube.com/NortonAbrasives](http://www.youtube.com/NortonAbrasives)