

**PRODUCT FEATURES**



**Pivoting Blade Guard**

All steel construction, with no springs or hinges, eliminates possible breakage.



**Heavy-Duty Box Frame**

Resists bending and flexing for a solid design.



**Eaton Transmission**

Hydro-static for infinitely variable forward and reverse speeds.



Combining all the features of the larger self-propelled Norton Clipper saw, this saw features a strong 13HP Honda engine in either manual or electric start. Constructed with a well-balanced and narrow box frame with right or left cutting capability, these flat saws are very versatile on any size job site.

**TECHNICAL SPECIFICATIONS**

PRODUCT #	C1320SM	C1320SS
UPC	701846 <b>27366</b>	701846 <b>27368</b>
Blade Guard Capacity – in. (mm)	20" (356)	20" (356)
Maximum Depth of Cut – in. (mm)	7-5/8" (193)	7-5/8" (193)
Arbor Size – in. (mm)	1" (25)	1" (25)
Blade Flange Diameter – in. (mm)	4-1/2" (114)	4-1/2" (114)
Blade Shaft RPM	2520 RPM	2520 RPM
Blade Shaft Diameter – in. (mm)	1-1/4" (32)	
Blade Shaft Bearings	Heavy Duty Pillow Block	
Blade Shaft Drive	4 Belts	
Blade Guard Attachment	Pivoting, All Steel	
Blade Control	Hand Wheel/Screw Feed	
Axle – Front – in. (mm)	3/4" (19)	
Axle – Rear – in. (mm)	3/4" (19)	
Wheels – Front D x W x B – in. (mm)	5" x 2" x 3/4" (127 x 50 x 19)	
Wheels – Rear D x W x B – in. (mm)	6" x 2" x 3/4" (152 x 50 x 19)	
Handle Bars/Adjustment Length	20-5/8" (530)	
Transmission	Eaton Hydrostatic	
Control	Roller Gear	
Speed	0-220 FPM	
Chassis	Heavy duty jig-welded box frame	
Power Source	Gasoline, Single Cylinder 4 Cycle	
Engine Type	Honda GX390	
Specifications	GX390K1QXC9	GX390K1QAE2
Maximum Horsepower	13 HP (9.5 kW) – *	
Net Horsepower	11 HP (8.2 kW) – *	
Displacement – cu. In. (l)	23.7 cu in (0.39)	
Bore – in. (mm)	3.5" (88)	
Stroke – in. (mm)	2.5" (64)	
Cylinders/Cycle	Single Cylinder 4 Cycle	
Fuel Capacity – gal. (l)	1.79 gal. (6.5 l)	
Oil Capacity – qt. (l)	1.16 qt. (1.1 l)	
Air Filter	Four Stage Honda	Two Stage Honda
Starter	Manual	Electric
Engine Cooling	Air	
SAW DIMENSIONS		
Height	40" (1,016)	40" (1,016)
Minimum Saw Length (Transport) – in. (mm)	56" (1,142)	56" (1,142)
Maximum Saw Length (Working) – in. (mm)	114" (2,896)	114" (2,896)
Maximum Pointer Length – in. (mm)	40" (1,016)	40" (1,016)
Frame Width – in. (mm)	17" (432)	17" (432)
Saw Width – in. (mm)	26" (660)	26" (660)
Front (Outside to Outside Wheel Width) – in. (mm)	14-3/16" (360)	14-3/16" (360)
Rear (Outside to Outside Wheel Width) – in. (mm)	15-1/4" (388)	15-1/4" (388)
Blade to Wall – in. (mm)	2-9/16" (65)	2-9/16" (65)
Wheel Base Length – in. (mm)	16-1/6" (407)	16-1/6" (407)
Weight Crated – lbs (kg)	425 (193)	445 (202)
Weight Uncrated – lbs (kg)	385 (175)	405 (175)
ACCESSORIES	UPC	SMART PART #
Water Tank Kit for 13HP & 20HP	701846 <b>28014</b>	<b>238001</b>

\*= DATA PROVIDED BY MOTOR/ENGINE MANUFACTURER  
GENUINE NORTON CLIPPER DIAMOND BLADE INCLUDED WITH SAW.



Water Tank Kit