

PRODUCT FEATURES



Gasoline Engine

Mounted with the dependable Honda 5.5HP engine for best performance.



Front Blade Mount

10" blade guard capacity. Additional weight helps keep the blade in the cut.



Fold-Down Design

Easy storage and transport.



Having a powerful Honda 5HP engine, the GC55 saw cuts faster than any other saw we have. The roller system allows you to roll on a concrete slab and cut a straight line without any difficulty. The weight of the saw is fantastic, making it an extremely portable machine.

– Tony Psencik, Suncoast Post-Tension, Ltd.



With a compact, light-weight design backed by the reliable Honda 5HP gasoline engine, the GC55 early entry saw is intended for a variety of applications. From green, cured or decorative concrete cutting to expansion joints, the features of this small push saw are hard to beat in a single saw. The low, wide profile of the frame, along with the front mount blade, contribute to producing a more disciplined cut. Now available in two models; our standard GC55 or our new GC55 VAC with Vacuum Attachment System. The GC55 and GC55 VAC include a wet kit for additional dust control.

TECHNICAL SPECIFICATIONS

PRODUCT #	GC55	GC55VAC	NEW
UPC	701846 30005	701846 02860	
Blade Guard Capacity – in. (mm)	10" (254)		
Maximum Depth of Cut – in. (mm)	3-1/2" (88)	1.85" (47)	
Arbor Size – in. (mm)	5/8" (15.9)		
Blade Flange Diameter – in. (mm)	3-5/64" (78)		
Blade Shaft RPM	3,000		
Blade Shaft Diameter – in. (mm)	7/8" (20)		
Blade Shaft Bearings	Sealed Radial Bearings		
Blade Shaft Drive	1 Cogged		
Blade Guard Attachment	All Steel		
Blade Control	Screw Feed		
Axle – Front – in. (mm)	55/64" (22)		
Axle – Rear – in. (mm)	55/64" (22)		
Wheels – Front – in. (mm) D x W x B	3-3/8" x 2-3/4" x 25/32" (85 x 70 x 20)		
Wheels – Rear – in. (mm) D x W x B	3-3/8" x 2-3/4" x 25/32" (85 x 70 x 20)		
Handle Bars/Adjustment Length – in. (mm)	6" (152.4)		
Control	Push		
Chassis	Heavy Duty Stamped Steel with Reinforcements		
Power Source	Single Cylinder 4 Cycle		
Motor/Engine Type	Honda GX160		
Specifications	GX160K1QXC9		
Maximum Horsepower	5.5 HP (4.1 kW) – *		
Net Horse Power	4.8 HP (3.6 kW) – *		
Voltage	NA		
Cycle/Current/Phase	NA		
Full Load Amps	NA		
Starting Amps	NA		
Displacement – cu. In (l)	9.9 cu in (0.16 l)		
Bore – in. (mm)	2.7" (68)		
Stroke – in. (mm)	1.8" (45)		
Cylinders/Cycle	Single Cylinder 4 Cycle		
Fuel Capacity – gal. (l)	.95 (3.6 l)		
Oil Capacity – qt. (l)	.63 (.6 l)		
Air Filter	Four Stage Cyclone		
Starter	Manual		
Engine Cooling	Forced Air		

SAW DIMENSIONS

Height – in (mm)	24-7/32" (615)	
Minimum Saw Length (Transport) – in. (mm)	32" (813)	34-1/2" (876)
Maximum Saw Length (Working) – in. (mm)	42-29/32" (1,090)	51-29/32" (1,318)
Maximum Pointer Length – in. (mm)	8-7/32" (209)	
Frame Width – in. (mm)	13-11/16" (348)	17-13/32" (442)
Saw Width – in. (mm)	18-1/8" (460)	
Front (Outside to Outside Wheel Width) – in. (mm)	8-21/32" (220)	
Rear (Outside to Outside Wheel Width) – in. (mm)	13" (330)	
Blade to Wall – in. (mm)	7-1/2" (190)	
Wheel Base Length – in. (mm)	19" (483)	
Weight Crated – lbs (kg)	135 (61)	145 (66)
Weight Uncrated – lbs (kg)	115 (52)	125 (57)

ACCESSORIES

	UPC	SMART PART #
GC55 Vacuum Attachment Accessory Kit	701846 02861	233933

(Includes: Fully assembled cutting arm with belt guard, belt, and blade shaft. Blade guard with vacuum port and skirt, stay level arm, and all hardware. Does not include GC55 saw, vacuum or wet kit.

*= DATA PROVIDED BY MOTOR/ENGINE MANUFACTURER

GENUINE NORTON CLIPPER DIAMOND BLADE INCLUDED WITH SAW.



Visit our YouTube page for more product information at:
www.youtube.com/NortonAbrasives