



# MULTIMASTER MM 500 Plus

## Oscillating MultiTools - MM 500

Our high-performance cordless MULTIMASTER 500 makes quick work of interior construction and renovation jobs. Includes a bimetal saw blade for working in wood, metal and plastic.

Product number: 7 229 67 62 09 0

### Details

- + Anti-vibration system: Permanently safe, pleasant working conditions with minimum vibrations and outstanding noise damping.
- + StarlockPlus tool mounting: Work faster and with higher precision thanks to 100% no-loss power transmission.
- + QuickIN: Tool change in under 3 seconds with a patented, tool-free, FEIN rapid-clamping system.
- + With the StarlockPlus tool mounting, you have access to around 100 FEIN accessories in the Starlock and StarlockPlus performance categories.
- + 350 W FEIN motor: Overload-proof, high-performance motor with high proportion of copper for higher cutting speed and rapid work progress.
- + Tacho generator: Constant speeds, even under load, and infinitely variable electronic speed control.
- + Metal drive head: High load capacity and maximum service life, since all drive head parts are made of metal.
- + Mechanical interface: For stationary use in the table or drill jig holders, or to attach depth stops.
- + Industrial cable: Large operating radius thanks to the 5 m, fine-stranded rubber-clad cable in industrial quality.

### Price includes

- + 1 universal E-Cut saw blade 1-3/4 in (44 mm) (type 152)
- + 1 tool case

### Product feature

- + Mechanical interconnection

### Technical data

TECHNICAL DATA

VIBRATION AND SOUND EMISSION VALUES



# FEIN

Power consumption	350 W	Sound pressure level LpA Measurement uncertainty of the measured value KpA	72 dB 3 dB
Oscillations	10,000 - 19,500 opm		
Tool mount	StarlockPlus	Sound power level LWA Measurement uncertainty of the measured value KWA	83 dB 3 dB
Tool change	QuickIN		
Range	2 x 1,7°	Peak sound value LpCpeak Measurement uncertainty of the measured value KpCpeak	84 dB 3 dB
Cable with plug	16 [5] ft[m]		
Weight	3.09 lbs		

## Application examples

