

FEATURES

Hydro Barrier: Full HPT coating on palm and fingers repels water to ensure secure grip in wet and oily conditions, while maintaining softness in extreme cold

Dynamic Performance: 15G nylon liner ensures comfort, precision, and adaptability for versatile performance in various tasks

Insulated Comfort: 7G acrylic inner liner provides 360° warmth down to -22°F/-30°C

Hygiene Defense: Treated with Sanitized Actifresh® to combat bacteria for prolonged comfort and freshness

Sure Seal: Knit wrist cuff ensures added security, comfort and functionality

Tried and Tested: Meets ANSI/ISEA 105 - CUT A2 | ABRASION 3 | PUNCTURE 2, EN 388 - 3231X and EN 511 - X2X, ensuring quality and safety

PYRAMEX° 💐 🖬 🕶 🗛 🛛 🖓 😘 🖄

P 800.736.8673 // F 901.861.4967 // W PYRAMEX.COM


GL902 CRAFTED FOR SAFETY, COATED FOR CONFIDENCE

Discover the GL902 insulated safety gloves with a 15G nylon liner, 360° 7G acrylic inner liner, and full HPT coating, along with Actifresh® treatment for bacteria defense and freshness.

MARKINGS

ANSI/ISEA 105 - CUT A2 | ABRASION 3 | PUNCTURE 2 EN388 - ABRASION 3 | CUT 2 | TEAR 3 | PUNCTURE 1 | CUT TDM-100 X

EN511 - CONVECTIVE COLD X | CONTACT COLD 2 | WATER IMPERMEABILITY X



SUGGESTED INDUSTRIES

Construction // Refrigeration // Commercial Fishing

GLOVE BREAKDOWN

Coating: Hydropellent Technology (HPT)			
Outer Liner: 15G Nylon			
Inner Liner: 7G 360° Acrylic			
Cuff: Nylon + Acrylic +Latex Elastic			

 \triangle WARNING: Cancer and Reproductive Harm –P65Warnings.ca.gov

This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

GLOVE SIZING

Small	Medium	Large	X-Large	2X-Large
7	8	9	10	11

PACKAGING

	Outer Polybag	Case	Made in
GL902	12 Pair	60 Pair	Pakistan

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.

Product markings may vary // Updated as of 08.24



TEAR



PUNCTURE



WATER



NSI/ISEA 105 EN3 A2 3 2 323

GL902

P 800.736.8673 // F 901.861.4967 // W PYRAMEX.COM