



Endeavor™ Plus ANSI • CSA •



RUBBER
NOSE PIECE



DIELECTRIC



CO-INJECTED
TEMPLES



ADJUSTABLE
NOSE PIECE



FOAM PADDED
OPTIONS

Built-in brow guard // Special dielectric hinge design // Curved co-injected temples // One-piece wraparound lens // Soft adjustable nosepiece // Foam padding is available in select options // Custom imprinting available

Black and Gray Temples | 5 Variations

- SBG9610S •• Clear
- SBG9610ST •• Clear **H2X** AF
- SBG9620S •• Gray
- SBG9620ST •• Gray **H2X** AF
- SBG9680S •• I/O Mirror

Black and Green Temples | 4 Variations

- SBGR9610S •• Clear
- SBGR9610ST •• Clear **H2X** AF
- SBGR9620S •• Gray
- SBGR9680S •• I/O Mirror



SBG96



SBP96

Black and Gray Temples with Foam Padding | 2 Variations

- SBG9610STMFP •• Clear **H2MAX** AF
- SBG9620STMFP •• Gray **H2MAX** AF

Black and Green Temples with Foam Padding | 2 Variations

- SBGR9610STMFP •• Clear **H2MAX** AF
- SBGR9620STMFP •• Gray **H2MAX** AF

Black and Pink Temples | 2 Variations

- SBP9610S •• Clear
- SBP9610ST •• Clear **H2X** AF

Endeavor™ Plus

General Specifications

Weight: 23.5 gm (without foam) 31.03gm (with foam)

Lens base: 9.5 curve

Lens size diagonal: 74 mm

Lens size vertical: 44.2 mm

Lens thickness: 1.8 mm

Overall length (lens - tip): 164 mm

Overall width (hinge - hinge): 124.7 mm

Materials

Lens: polycarbonate

Temples: polycarbonate & thermoplastic elastomers (TPE)

Hinge: polycarbonate

Side shields: polycarbonate

Nosepiece: thermoplastic rubbers (TPR)

Foam gasket: nylon with ethylene-vinyl acetate(EVA) foam

Part No.	Lens Marking	Temple Marking
SBG9610S	P Z87 + U6	P Z87 + / P c SEI Z94.3
SBG9610ST	P Z87 + U6	P Z87 + / P c SEI Z94.3
SBG9610STMFP	P Z87 + U6 X	P Z87 + / P c SEI Z94.3
SBG9620S	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3
SBG9620ST	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3
SBG9620STMFP	P Z87 + U6 L2.5 X	P Z87 + / P c SEI Z94.3
SBG9680S	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3
SBGR9610S	P Z87 + U6	P Z87 + / P c SEI Z94.3
SBGR9610ST	P Z87 + U6	P Z87 + / P c SEI Z94.3
SBGR9610STMFP	P Z87 + U6 X	P Z87 + / P c SEI Z94.3
SBGR9620S	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3
SBGR9620STMFP	P Z87 + U6 L2.5 X	P Z87 + / P c SEI Z94.3
SBGR9680S	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3
SBP9610S	P Z87 + U6	P Z87 + / P c SEI Z94.3
SBP9610ST	P Z87 + U6	P Z87 + / P c SEI Z94.3

Lens Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

X: Tested Anti-fog

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light

L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

c SEI Z94.3: CAN/CSA standard for eye and face protection devices