



HALF FRAME



Vented
Frame



Adjustable
Nose Piece



Adjustable
Temples



Co-injected
Temples



H2X
Anti-fog



H2MAX
Anti-fog



MIL-PRF
-32432

VENTURE 3®

ANSI/ISEA Z87.1-2020 • CE/UKCA EN166 • CAN/CSA Z94.3-20 • MIL-PRF-32432 •

Soft, adjustable nose piece // Ventilated frame //
Adjustable co-injected rubber temples // Passes
Ballistic MIL-PRF-32432 High Velocity Impact
standards // Custom imprinting available

Lens and Temples | 9 Variations

SB5710D	Clear
SB5710DT	Clear H2X AF
SB5710DTM	Clear H2MAX AF
SB5720D	Gray
SB5720DT	Gray H2X AF
SB5730D	Amber
SB5760D	Infinity Blue
SB5770D	Silver Mirror
SB5780D	I/O Mirror



Materials

Lens: Polycarbonate
Nose Piece: Polycarbonate + PVC
Side Shield: Polycarbonate
Temples: Polycarbonate + Thermoplastic
Screw: Stainless Steel
Hinge: Polycarbonate
Sleeve: Polycarbonate
Frame: Polycarbonate



Part No.	Lens Marking	Temple Marking	Lens Marking Symbols	Temple Marking Symbols	Measurements
SB5710D	P + U6	P Z87 + / P c SEI Z94.3	P: Manufacturer's mark	P: Manufacturer's mark	Weight: 28 gm
SB5710DT	P + U6	P Z87 + / P c SEI Z94.3	+: High impact	Z87: ANSI/ISEA Z87.1-2020 standard for eye and face protection devices	PD: 68 mm
SB5710DTM	P + U6 X	P Z87 + / P c SEI Z94.3	S: Special Purpose	+: High impact	Bridge: 12.8 mm
SB5720D	P + U6 L2.5	P Z87 + / P c SEI Z94.3	X: Tested Anti-fog	c SEI Z94.3: CAN/CSA Z94.3-20 standard for eye and face protection devices	Lens base: 9.5 curve
SB5720DT	P + U6 L2.5	P Z87 + / P c SEI Z94.3	UV Filter Transmittance		Lens size diagonal: 82 mm
SB5730D	P + U6	P Z87 + / P c SEI Z94.3	U6: .01% max effective far UV • .1% max near UV		Lens size vertical: 46.6 mm
SB5760D	P + S	P Z87 + / P c SEI Z94.3	Visible Light Filters		Lens thickness: 2.3 mm
SB5770D	P + S	P Z87 + / P c SEI Z94.3	L1.7: 55% Max. Visible Light		Overall length (lens - tip): 150 - 163 mm
SB5780D	P + U6 L1.7	P Z87 + / P c SEI Z94.3	L2.5: 29% max visible light		Overall width (hinge - hinge): 139.4 mm
			L2.5: 29% max visible light		Closest point between lens: 13.1 mm

Product markings may vary // Updated as of 10.24