

**18V LXT® LITHIUM-ION BRUSHLESS
CORDLESS 1/3 SHEET FINISHING SANDER,
AWS® CAPABLE, TOOL ONLY**



**NEW TOOL OVERVIEW
XOB03Z**

LXT® BRUSHLESS

FEATURES

- One-touch electronic speed control button provides fast, medium and low settings
- Efficient through-the-pad dust collection system for a cleaner work environment
- Quick change clamp for faster sandpaper installation
- Auto-start Wireless System (AWS®) utilizes Bluetooth® technology for wireless power-on/off communication between tool and optional dust extractor
- AWS® capable with Auto-start Wireless Transmitter (part no. 198901-5) sold separately
- Equipped with Star Protection Computer Controls™ to protect against overloading, over-discharging and over-heating
- Compatible with Makita 18V Lithium-Ion batteries with a Star symbol (battery sold separately)

SPECIFICATIONS

Voltage	18V
Form Factor (LXT)	18V LXT®
Battery	18V LXT® Lithium-Ion
Power Type	Cordless
Motor Type	Brushless
Orbits Per Minute (3 speed)	4,000, 8,000, 12,000 OPM
Maximum orbits per minute	12,000 OPM
Orbit Diameter	1/16"
Vibration (m/s²)	3.6
Pad Size	3-5/8" x 7-1/4"
Abrasive Paper Size	3-5/8" x 9"
Net Weight (with battery, sold separately)	4.9 lbs.
Overall Length	13-1/4"
Shipping Weight	4.9 lbs.
UPC Code	088381-752152

STANDARD EQUIPMENT

- Punch Plate (451271-6)
- Dust Bag (140441-9)
- Battery Protector (422807-8)



PRODUCT HIGHLIGHTS



SPEED

Three speed settings (4,000/8,000/12,000 OPM) engineered for faster material removal



INNOVATION

Motor and battery location reduces fluttering and helps achieve an evenly finished surface



COMFORT

Ergonomically designed body and grip for increased operator comfort



PERFORMANCE

1/16" orbit action engineered for faster sanding and swirl-free finish

RELATED PRODUCTS

1. 18V LXT® Lithium-Ion Rapid Optimum Charger (DC18RC)
2. 18V LXT® Lithium-Ion 6.0Ah Battery (BL1860B)
3. 18V LXT® Lithium-Ion Compact 2.0Ah Battery (BL1820B)
4. 18V LXT® Random Orbit Sander (XOB01Z)
5. 18V LXT® Brushless 3-1/4" Planer, AWS® Capable (XPK02Z)

1



2



3



4



5

