



# ACRYLIC HIGH-GLOSS OR MATTE FLOOR POLISH

**Choose from  
High Gloss or  
Low Gloss  
for Concrete,  
Masonry and  
Tile Floors**

*Extreme protection against foot traffic, abrasion, and scuffing on difficult floor surfaces. Areas of wear can be reapplied without redoing the entire floor.*



**Designed Specifically for Sealed Stone,  
Tile, Masonry and Concrete Surfaces**

- Regular Use Extends the Life of the Sealer
- Removable with Conventional Wax/Polish Stripper
- Ideal for Decorative Concrete & Vinyl Floors



**Professional Results...GUARANTEED!**

800-486-1414 • [www.glaze-n-seal.com](http://www.glaze-n-seal.com)



# ACRYLIC HIGH-GLOSS OR MATTE FLOOR POLISH

## FORMULATED ESPECIALLY FOR QUARRY TILE • MEXICAN & PAVER TILE • SLATE • FLAGSTONE COLORED & HARD TROWELED CONCRETE • BRICK • TERRAZZO STAMPED CONCRETE • FRENCH PROVINCIAL TILE

### PRODUCT DESCRIPTION

**Glaze 'N Seal Floor Polish** is a product of revolutionary new chemistry, designed to produce either a high or low gloss finish with extreme protection against foot traffic, abrasion and scuffing on difficult floor surfaces. It is easy to apply and completely safe to use indoors on dense tile or previously sealed tile.

### SPECIAL FEATURES

- Regular use extends the life of the sealer.
- Made especially for tile and masonry type surfaces. Ideal for decorative and color stained concrete.
- Easily reapplied on heavy traffic areas
- Removable with conventional wax/polish stripper
- Excellent slip resistance. Coefficient of friction exceeds 0.5.
- Wear resistance 5-7 KHN, compared to industry standard of 2-4 KHN.

### PRODUCT INFORMATION

**Glaze 'N Seal Floor Polish** is an acrylic polymer floor polish that can be applied and reapplied with ease. The more coats, the greater protection. **Glaze 'N Seal Floor Polish** can be reapplied to heavy traffic areas without needing to polish the entire floor due to the "self leveling" properties of the polish.

### PREPARATION

The floor surface should be clean and dry. Remove all dirt, defective waxes, coatings and efflorescence. Porous surfaces and grout must be pre-sealed with a sealer before polishing (*such as GNS "Wet Look" Lacquer, Multi-Purpose Sealer or OLÉ*) prior to using the polish. On porous surfaces always apply a sealer before applying floor polish.

### APPLICATION PROCEDURE

Apply **Glaze 'N Seal Floor Polish** with a sponge mop, or standard wax applicator. Three to five light coats should be applied initially. Avoid creating excess foam when sponge is used. Do NOT puddle polish. Allow the first coat 30-50 minutes (until dry to the touch) before applying the second coat. Additional coats will give additional protection.

### MAINTENANCE/REPAIR

Do not allow polish to wear through. To clean, damp mop finished surface with clean water regularly. Occasionally, add 2-4 ounces of **Glaze 'N Seal Neutral Cleaner** to wash water to aid cleaning of oily dirt and soil pickup. Alkaline cleaners may dull the surface. Do not allow other cleaning agents onto the finished floor. **Glaze 'N Seal Floor Polish** may be repaired when scratched or worn by reapplication to the affected areas only. It is normally not necessary to treat the entire area.

### STRIPPING

This is normally not required as this non-yellowing formula can last for years when maintained as directed. Polish, if necessary, can be removed with **Glaze 'N Seal Heavy Duty Cleaner** or conventional wax stripper.

### COVERAGE

Coverage will average 500 to 1,000 square feet per gallon depending on the surface.

### LIMITATIONS

Do NOT shake or stir. Do not allow to freeze in its liquid state. For interior use only. Recommended for nonabsorbent surfaces only. Pre seal absorbent surfaces before use, including grout.

**WARRANTY:** Glaze 'N Seal product liability, either expressed or implied, is limited solely to the replacement of this product when proven to be defective and does not include any labor costs or consequential damages. It is the user's responsibility to determine the safety, toxicity and suitability of this product.

**SAFETY INFORMATION:** This product is nonhazardous according to OSHA 29CFR 1910.1200. May cause mild skin and eye irritation.

**STORAGE:** Store in closed container. Dispose of contents/container in accordance with local regulations.

**CONTAINS:** Water (7732-18-5), acrylic polymer, diethylene glycol monoethyl ether (111-90-0), ethylene glycol (107-21-1), tributoxethyl phosphate (78-51-3), balance is non-hazardous trade secret components, TSRN: FP-522. For further information refer to the SDS (Safety Data Sheet).

KEEP OUT OF THE REACH OF CHILDREN



MADE IN USA



GLAZE-N-SEAL.COM



Quality Products for Concrete, Tile and Masonry

Glaze 'N Seal Products Inc., Irvine, CA • www.glaze-n-seal.com