





PACKAGE



TECHNICAL CHARACTERISTICS


































- Maximum length of cut 150 cm (59").
- Maximum depth of cut 55 mm (2 1/8") in single pass; 65 mm (2 1/2") in double pass.
- Diamond blade Ø 250 mm (10").
- Plunge cut and adjustable cutting depth.
- Heavy Duty water pump. High capacity double jet water cooling.
- Sliding bar, pivots and disc cover in aluminum.
- Easy-to-remove aluminum work benches for easy cleaning and maximum sturdiness.
- Coated metal frame.
- Re-adjustable aluminum square.

- Motor moves on 4 polypropylene pulleys.; each pulley is reinforced with 2 inside bearings.
- Pulleys are easy to re-adjust (tighten): avoid play and confer long lasting precision of cut.
- Motor held by galvanized metal frame.
- Tiling legs.
- Tilting movement (0-47°) for 45° angle cut (jolly).
- Available accessories: extra side square, self-standing side bench with rollers, 4 wheels + 2 handles kit, wheel feed kit.
- Supplied with Ø 250 mm (10") diamond disc for porcelain tiles, user manual, keys kit, dressing

MODEL SPECIFICATIONS

Part No.			M	M			•	
225MS 150EU	8024648089809	1	230 V 50 Hz	Single-phase	1,5 HP / 1,1 kW	2800	250 mm 10"	2800
225MS 150BR	8024648089793	1	230 V 60 Hz	Single-phase	1,5 HP / 1,1 kW	3360	250 mm 10"	3360
225MS 150US	8024648089823	1	110 V 60 Hz	Single-phase	1,5 HP / 1,1 kW	3360	250 mm 10"	3360
225MS 150GB	8024648089816	1	110 V 50 Hz	Single-phase	1,5 HP / 1,1 kW	2800	250 mm 10"	2800

CUTTING SPECIFICATIONS AND MACHINE DIMENSIONS / WEIGHT

CUTING SPECIFICATIONS AND MACRIME DIMENSIONS / WEIGHT											
	Model		‡								2
	BOLT 150	250 mm 10"	55 mm 2 1/8"	30 mm 1 3/16"	150 cm 59"	∞	105x105 cm 41 3/8"x 41 3/8"	180×56X h50 cm 71"x22"x h19 5⁄8"	56 Kg 123 5 lbs	195x65x h55 cm 76 3/4"x25 1/2"x h 21 5/8"	72 Kg 158.7 lbs

