

**SAFETY DATA SHEET**

REVISION DATE: 06-10-2015

SUPERSEDES: None

**SECTION 1: IDENTIFICATION OF THE PRODUCT AND SUPPLIER****PRODUCT INFORMATION**

PRODUCT: POWERGROUT - SABLE  
PRODUCT DESCRIPTION: Cement  
INTENDED USE: Adhesive  
PRODUCT IDENTIFIER: 839291PM

**COMPANY INFORMATION**

H.B. Fuller Construction Products Inc.  
1105 S. Frontenac Street  
Aurora, IL 60504  
Phone: 1-800-552-6225

Medical Emergency Phone Number (24 Hours): 1-888-853-1758  
Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

**SECTION 2: HAZARDS IDENTIFICATION****GHS Hazard Symbols:**

**GHS Signal Word:** Danger  
**GHS Classification:** Serious Eye Damage/Eye Irritation Category 1; Skin Sensitisation Category 1; Carcinogenicity Category 1A; Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 1; Skin Corrosion/Irritation Category 2  
**GHS Hazard Phrases:** Causes skin irritation.; May cause an allergic skin reaction.; Causes serious eye damage.; May cause cancer.; Causes damage to organs through prolonged or repeated exposure.  
**GHS Precautions:**  
**Safety Precautions:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.  
**First Aid Measures:** IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Immediately call a POISON CENTER or doctor/physician. Get medical advice/attention if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.  
**Storage:** Store locked up.  
**Disposal:** Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

**SAFETY DATA SHEET**

Chemical Name	CAS #	PERCENT	Classification	Note
Crystalline silica	14808-60-7	30 - 50	Carc. 1A; H350 STOT RE 1; H372	* (see below)
Alumina cement	65997-16-2	10 - 30	Eye Dam. 1; H318 Skin Irrit. 2; H315	
Calcium sulfate, hemihydrate	26499-65-0	10 - 30	Eye Irrit. 2; H319 Skin Irrit. 2; H315 STOT SE 3; H335	* (see below)
Portland cement	65997-15-1	10 - 30	Eye Dam. 1; H318 Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335	* (see below)
Titanium dioxide	13463-67-7	1 - 5	Carc. 2; H351	* (see below)
Iron oxide (Fe3O4)	1317-61-9	1 - 5	Self-heat. 1; H251	
L-Tartaric acid	87-69-4	0.1 - 1	Acute Tox. 4; H302 Eye Irrit. 2; H319 Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335	

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for exposure limit guidelines.

**SECTION 4: FIRST AID MEASURES**

**IF IN EYES:** Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.

**IF ON SKIN:** Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

**IF INHALED:** Remove to fresh air. Restore breathing, if necessary. Call a physician if symptoms persist.

**IF SWALLOWED:** Severely irritating. Do not induce vomiting. Seek medical attention immediately. Drink 2 glasses of water or milk to dilute. Do not give anything by mouth to an unconscious person.

**SECTION 5: FIRE FIGHTING MEASURES**

**EXTINGUISHING MEDIA:**

Use water spray, foam, dry chemical or carbon dioxide.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:**

There is a possibility of pressure buildup in closed containers when heated. Water spray may be used to cool the containers. Material will burn in a fire.

**SPECIAL FIRE FIGHTING INSTRUCTIONS:**

Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.

**HAZARDOUS COMBUSTION PRODUCTS:**

Carbon dioxide, Carbon monoxide Aluminum oxide Sulfur containing gases

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**SPECIAL PROTECTION:**

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred.

**SAFETY DATA SHEET**

**METHODS FOR CLEAN-UP:** Avoid creating dusts. Eliminate ignition sources. If a vacuum is used, ensure that the material is wetted or otherwise treated so an explosive dust atmosphere is not created within the vacuum.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

**SECTION 7: HANDLING AND STORAGE**

**Handling:** Avoid contacting and avoid breathing the material. Use only in a well ventilated area. Avoid breathing material.

**Storage:** Store in a cool, dry place.  
Consult the Technical Data Sheet for specific storage instructions.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**EXPOSURE LIMITS:**

Chemical Name	Note	ACGIH EXPOSURE LIMITS	OSHA PEL
Crystalline silica	* (see below)	0.025 mg/m <sup>3</sup> TWA (respirable fraction)	((250)/(%SiO <sub>2</sub> + 5) mppcf TWA (respirable)); ((10)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA (respirable)); ((30)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA (total dust))
Diatomaceous earth	* (see below)	No data available.	20 mppcf TWA; ((80)/(% SiO <sub>2</sub> ) mg/m <sup>3</sup> TWA)
Calcium sulfate, hemihydrate	* (see below)	No data available.	15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction)
Portland cement	* (see below)	1 mg/m <sup>3</sup> TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)	15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction)
Calcium carbonate	* (see below)	No data available.	15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction)
Iron oxide	* (see below)	5 mg/m <sup>3</sup> TWA (respirable fraction)	10 mg/m <sup>3</sup> TWA (as fume)
Aluminum oxide	* (see below)	No data available.	15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction)
Titanium dioxide	* (see below)	10 mg/m <sup>3</sup> TWA	15 mg/m <sup>3</sup> TWA (total dust)
Iron oxide (Fe <sub>3</sub> O <sub>4</sub> )		No data available.	10 mg/m <sup>3</sup> TWA (as fume)
Calcium sulfate	* (see below)	10 mg/m <sup>3</sup> TWA (inhalable fraction)	15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction)

**ENGINEERING CONTROL METHODS:**

**VENTILATION:** Use local exhaust ventilation or other engineering controls to minimize exposures.

**EYE PROTECTION:** Wear safety glasses with side shields when handling this product.  
Wear additional eye protection such as chemical splash goggles

**SAFETY DATA SHEET**

	and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash station available.
SKIN PROTECTION:	Avoid skin contact by wearing chemically resistant gloves and long sleeved shirt. An apron may be appropriate if splashing can occur.
GLOVES:	Nitrile
RESPIRATORY PROTECTION:	Respiratory protection may be required to avoid overexposure when handling this product. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. NIOSH approved air purifying respirator with dust/mist filter. Respirators should be selected by and used following requirements found in OSHA's respirator standard (29 CFR 1910.134).

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

PHYSICAL STATE:	Solid
COLOR:	Opaque Brown
ODOR:	Odorless
ODOR THRESHOLD:	Not established
pH:	Not established
FREEZING/MELTING POINT (deg. C):	Not established
BOILING POINT (deg. C):	Not established
FLASH POINT:	Non flammable
EVAPORATION RATE:	Not established
FLAMMABILITY:	Not a flammable solid or gas
UPPER EXPLOSIVE LIMIT (% in air):	Not established
LOWER EXPLOSIVE LIMIT (% in air):	Not established
VAPOR PRESSURE (mm Hg):	Not established
VAPOR DENSITY:	Not established
WEIGHT PER GALLON (lbs.):	11.00
SPECIFIC GRAVITY:	1.310
SOLUBILITY:	Not established
OCTANOL/WATER COEFFICIENT:	Not established
AUTOIGNITION TEMPERATURE:	Not established
DECOMPOSITION TEMPERATURE:	Not established
VISCOSITY:	No data available.
SOLIDS (% by weight):	100.0
VOC, weight percent	0.00

**SECTION 10: STABILITY AND REACTIVITY**

STABILITY:	Stable under normal conditions.
CHEMICAL INCOMPATIBILITY:	Not established
HAZARDOUS POLYMERIZATION:	Will not occur.
HAZARDOUS DECOMPOSITION PRODUCTS:	Carbon monoxide, carbon dioxide Aluminum oxide Sulfur containing gases

**SECTION 11: TOXICOLOGICAL INFORMATION**
**Component Toxicity / Toxicology Data:**

COMPONENT NAME	LD50/LC50
Crystalline silica	ORAL LD50 RAT 500 MG/KG

**SAFETY DATA SHEET**

Calcium carbonate	ORAL LD50 RAT 6,450 MG/KG
Iron oxide	ORAL LD50 RAT > 10,000 MG/KG
Aluminum oxide	ORAL LD50 RAT > 5,000 MG/KG
Titanium dioxide	ORAL LD50 RAT > 10,000 MG/KG
Iron oxide (Fe <sub>3</sub> O <sub>4</sub> )	ORAL LD50 RAT > 10,000 MG/KG
Calcium sulfate	ORAL LD50 RAT > 3,000 MG/KG

**This product is a mixture. Unless noted, the information below is based on components.**

Skin corrosion / irritation: Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

Serious eye damage / irritation :Can cause moderate irritation, tearing and reddening.

Respiratory / skin sensitization: May cause an allergic skin reaction.

Germ cell mutagenicity: No data available.

Carcinogenicity: Contains a material that may cause cancer.

Reproductive toxicity: Contains a substance that is a possible reproductive hazard based on animal studies.

Specific target organ toxicity-single exposure: No data available.

Respiratory irritation / Narcotic effects: May cause respiratory irritation.

Specific target organ toxicity-repeated exposure: Causes damage to organs through prolonged or repeated exposure.

Target organs potentially affected by exposure: Lungs

Aspiration hazard: No data available.

Medical Conditions Aggravated by Exposure: Lung disease

**SECTION 12: ECOLOGICAL INFORMATION**

OVERVIEW:	No ecological information available for this product.
MOBILITY:	No data available.
PERSISTENCE:	No data available.
BIOACCUMULATION:	No data available.

**This product has not been tested for ecological effects. Relevant information for components is listed below:**

Component:	Ecotoxicity values:
Calcium sulfate	<b>Acute Toxicity (Fish):</b> 96 Hr LC50 Lepomis macrochirus: 2980 mg/L [static]; 96 Hr LC50 Pimephales promelas: >1970 mg/L [static] <b>Acute Toxicity (Daphnia):</b> Not established <b>Acute Toxicity (Algae):</b> Not established

**SECTION 13: DISPOSAL CONSIDERATIONS**

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Dispose of in an approved landfill. Consult your state, local or provincial authorities and your local waste vendor for more restrictive requirements.

**SECTION 14: TRANSPORT INFORMATION**

Consult Bill of Lading for transportation information.

**SAFETY DATA SHEET**

US DOT: NOT REGULATED  
IATA: NOT REGULATED

**SECTION 15: REGULATORY INFORMATION****INVENTORY STATUS**

U.S. EPA TSCA: This product is in compliance with the Toxic Substances Control Act's Inventory requirements.

CANADIAN CEPA DSL: The components of this product are included on the DSL or are exempt from DSL requirements.

EUROPEAN REACH: As a result of the introduction of REACH into Europe, this product cannot be imported into Europe unless the REACH requirements are met.

AUSTRALIA AICS: This product contains a component that is not on the Australian Inventory (AICS).

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at [reg.request@hbfuller.com](mailto:reg.request@hbfuller.com) to request an export review.

**FEDERAL REPORTING****EPA SARA Title III Section 313**

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name	CAS#	%
	1344-28-1	1 - 5
Lithium carbonate	554-13-2	0.1 - 1

**STATE REPORTING****Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986:**

Unless listed below, this product does not contain known levels of any chemical known to the State of California to cause cancer or reproductive harm.

Chemical Name/List		CAS	Percent
Quartz	(Carcinogen)	14808-60-7	30 - 50
Titanium dioxide	(Carcinogen)	13463-67-7	1 - 5
Nickel	(Carcinogen)		0.01 - 0.1
Nickel	(Carcinogen)	7440-02-0	< 10 ppm
Arsenic compounds (inorganic)	(Carcinogen)		< 10 ppm
Lithium carbonate	(Developmental toxin)	554-13-2	0.1 - 1
Methanol	(Developmental toxin)	67-56-1	0.01 - 0.1

**Substances of Very High Concern (SVHC) Content:**

Unless listed below, this product does not contain SVHC's.

**SECTION 16: OTHER INFORMATION**

SDS VERSION DATE: 06-10-2015

**SAFETY DATA SHEET**

---

This Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

HMIS RATING: HEALTH -- 2 FLAMMABILITY -- 1 REACTIVITY -- 0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B. Fuller Construction Products, Inc. from its suppliers, and because H.B. Fuller Construction Products, Inc. has no control over the conditions of handling and use, H.B. Fuller Construction Products, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B. Fuller Construction Products, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Construction Products, Inc. products to comply with all applicable federal, state and local laws and regulations.